



Terminal product specification	01-10-2012	Diesel 10ppm
---------------------------------------	-------------------	---------------------

Property	Unit	Minimum	Maximum	Test method
Cetane number		51,0		EN ISO 5165
Cetane index		46,0		EN ISO 4264
Density at 15 °C	kg/m3	820,0	845,0	EN ISO 3675
Polycyclic aromatic compounds	% m/m		8	EN ISO 12916
Sulfur content	mg/kg		10,0	EN ISO 20846
Flash point	°C	>55		EN ISO 22719
Carbon residue on 10% distillation residue	% m/m		0,30	EN ISO 10370
Ash content	% m/m		0,01	EN ISO 6245
Water content	mg/kg		200	EN ISO 12937
Total contamination	mg/kg		24	EN ISO 12662
Copper strip corrosion (3 hrs. at 50 °C)	Rating	Class 1		EN ISO 2160
Oxidation stability	g/m3		25	EN ISO 12205
	h	20		EN 15751
Lubricity, corrected wear scare diameter (wsd 1,4) at 60 °C	µm		460	EN ISO 12156-1
Viscosity at 40 °C	mm²/s	2,00	4,50	EN ISO 3104
Distillation % (v/v) recovered at 250 °C % (v/v) recovered at 350 °C 95 % (v/v) recovered at	% v/v % v/v °C	85	<65 360	EN ISO 3405
Fatty acid methyl ester (FAME) content	% v/v		7	EN ISO 14078
CFPP	Summer*	°C	-5	EN 116
	Intermediate**	°C	-11	
	Winter***	°C	-20	
Cloud point	Summer*	°C	4	EN 116
	Intermediate**	°C	0	
	Winter***	°C	-7****	

* Summer: April 15th - September 30th
 ** Intermediate: October 1st - November 15th / March 1st - April 14th
 *** Winter: November 16th - Februari 28th
 **** -5 including effective WASA