



| | | |
|---------------------------------------|-------------------|------------------|
| Terminal product specification | 01-10-2012 | Superplus |
|---------------------------------------|-------------------|------------------|

| Property | Unit | Minimum | Maximum | Test Method |
|--|----------------------------|------------------|---------|-------------------|
| Research Octane Number RON | | 98,0 | | EN ISO 5164 |
| Motor Octane Number MON | | 88,0 | | EN ISO 5163 |
| Lead content | mg/l | | 5,0 | EN237 |
| Density at 15 °C | kg/m ³ | 720,0 | 775,0 | EN ISO 3675 |
| Sulfur content | mg/kg | | 10,0 | EN ISO 20846 |
| Oxidation stability | min. | 360 | | EN ISO 7536 |
| Existent gum content (Solvent washed) | mg/100ml | | 5 | EN ISO 6246 |
| Copper strip corrosion (3 hrs. at 50 °C) | Rating | Class 1 | | EN ISO 2160 |
| Appearance | | Clear and bright | | Visual inspection |
| Hydrocarbon type content | Olefins | % v/v | 18,0 | EN 15417 |
| | Aromatics | % v/v | 35,0 | |
| Benzene content | % v/v | | 1,00 | EN 238 |
| Oxygen content | % m/m | | 2,7 | EN 1601 |
| Oxygenates content | Methanol | % v/v | 3,0 | EN 1601 |
| | Ethanol | % v/v | 5,0 | |
| | iso-propyl alcohol | % v/v | 10,0 | |
| | iso-butyl alcohol | % v/v | 10,0 | |
| | tert-butyl alcohol | % v/v | 7,0 | |
| | ethers (5 or more C atoms) | % v/v | 15,0 | |
| | other oxygenates | % v/v | 10,0 | |
| Vapour pressure | Summer* | kPa | 45,0 | EN 13016-1 |
| | Winter** | kPa | 65,0 | |
| Vapour Lock Index | April + October | index | 1200 | |
| Distillation % evaporated at 70 °C E70 % evaporated at 70 °C E70 % evaporated at 100 °C E100 % evaporated at 150 °C E150 Final Boiling Point FBP Distillation residue | Summer* | % v/v | 20,0 | EN ISO 3405 |
| | | Winter** | % v/v | |
| | % v/v | 46,0 | 71,0 | |
| | % v/v | 75,0 | | |
| | ° C | | 210 | |
| | % v/v | | 2 | |

* Summer: May 1st - September 30th
 ** Winter: October 1st - April 30th
 More stringent seasonal specifications for RVP will be applied and are available at request